

KEY FEATURES



- High power handling: 1000 W program power
- 2,5" copper wire voice coil
- Malt Cross[®] Cooling System
- Low power compression losses
- High sensitivity: 96 dB (1W / 1m)

- Optimized pressed steel frame
- FEA optimized magnetic circuit
- Waterproof cone with treatment for both sides of the cone
- Optimized for 2 or 3 way PA systems and line arrays for ultimate professional applications



TECHNICAL SPECIFICATIONS

Nominal diameter	250 mm	10 in
Rated impedance		8 Ω
Minimum impedance		7,2 Ω
Power capacity ¹		500 W _{AES}
Program power ²		1.000 W
Sensitivity	96 dB	1W / 1m @ Z _N
Frequency range		70 - 5.000 Hz
Voice coil diameter	63,5 mm	2,5 in
Bl factor		17,6 N/A
Moving mass		0,047 kg
Voice coil length		19,5 mm
Air gap height		9,5 mm
X _{damage} (peak to peak)		40 mm

THIELE-SMALL PARAMETERS³

Resonant frequency, f _s		70 Hz
D.C. Voice coil resistance, R _e		5,7 Ω
Mechanical Quality Factor, Q _{ms}		10,1
Electrical Quality Factor, Q _{es}		0,38
Total Quality Factor, Q _{ts}		0,37
Equivalent Air Volume to C _{ms} , V _{as}		18,8 l
Mechanical Compliance, C _{ms}		109 μm / N
Mechanical Resistance, R _{ms}		2,1 kg / s
Efficiency, η ₀		1,7 %
Effective Surface Area, S _d		0,035 m ²
Maximum Displacement, X _{max} ⁴		8 mm
Displacement Volume, V _d		280 cm ³
Voice Coil Inductance, L _e @ 1 kHz		1,1 mH


Notes:

¹ The power capacity is determined according to AES2-1984 (r2003) standard.

² Program power is defined as power capacity + 3 dB.

³ T-S parameters are measured after an exercise period using a preconditioning power test. The measurements are carried out with a velocity-current laser transducer and will reflect the long term parameters (once the loudspeaker has been working for a short period of time).

⁴ The X_{max} is calculated as (L_{vc} - H_{ag})/2 + (H_{ag}/3,5), where L_{vc} is the voice coil length and H_{ag} is the air gap height.



Note: On axis frequency response measured with loudspeaker standing on infinite baffle in anechoic chamber, 1W @ 1m

MOUNTING INFORMATION

Overall diameter	258 mm	10,2 in
Bolt circle diameter	241 mm	9,5 in
Baffle cutout diameter:		
- Front mount	230 mm	9,1 in
Depth	125 mm	4,9 in
Net weight	5,7 kg	12,6 lb
Shipping weight	6,1 kg	13,5 lb

DIMENSION DRAWING

